

CASING CUTTER SPECIFICATIONS

Part Number	Cutter OD (in.)	Net Explosive Content (g)	Explosive Class	Temperature Rating (°F) [°C]	UN ID	Hazard Class	EX (DOT) Number	EC Certificate	Pressure Rating (psi)	Casing OD (in.)	Wall Thickness (in.)
3500T301 PA (RED)	3.500	59	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.10.0029	7,500	4½	0.357
4250T301PA (STD)	4.250	76	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.10.0029	7,500	5½	0.415
4250T301 PA (RED)	4.250	76	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.10.0029	7,500	5½	0.415
5800T301PA (STD)	5.800	97.6	HMX	400 [204]	0440	1.4D	2013040280	0080.EXP.10.0029	7,500	7	0.540
6250T301PA (STD)	6.250	97.6	HMX	400 [204]	0440	1.4D	2013040280	0080.EXP.10.0029	7,500	7	0.317
5250T201 (PRM)	5.250	139	HMX	400 [204]	0059	1.1D	2003030306	0080.EXP.09.0018	18,000	7	0.500
5375T201 (PRM)	5.375	139	HMX	400 [204]	0059	1.1D	2003030306	0080.EXP.09.0018	18,000	7	0.500
5700T201 (PRM)	5.700	139	HMX	400 [204]	0059	1.1D	2003030306	0080.EXP.09.0018	18,000	7	0.500
5250T301 (PRM)	5.250	97.6	HMX	400 [204]	0440	1.4D	2013040280	0080.EXP.09.0015	18,000	7	0.408
5375T301 (PRM)	5.375	97.6	HMX	400 [204]	0440	1.4D	2013040280	0080.EXP.09.0015	18,000	7	0.408
5700T301 (PRM)	5.700	97.6	HMX	400 [204]	0440	1.4D	2013040280	0080.EXP.09.0015	18,000	7	0.408
6250T301PA (STD)	6.250	97.6	HMX	400 [204]	0440	1.4D	2013040280	0080.EXP.10.0029	7,500	7⅝	0.430
6600T301PA (STD)	6.600	97.6	HMX	400 [204]	0440	1.4D	2013040280	0080.EXP.10.0029	7,500	7⅝	0.430

HMX explosive for all cutters rated at 400° for 1 hr.