

COILED TUBING CUTTER SPECIFICATIONS

Part Number	Cutter OD (in.)	Net Explosive Content (g)	Explosive Class	Temperature Rating (°F) [°C]	UN ID	Hazard Class	EX (DOT) Number	EC Certificate	Pressure Rating (psi)	Pipe OD (in.)	Pipe Weight (lbm/ft)
0687T001 (PRM)	0.687	2	HMX	400 [206]	0440	1.4D	2003030305	0080.EXP.09.0031	18,000	1.000	0.788–1.040
0800T001 (PRM)	0.800	3	HMX	400 [206]	0440	1.4D	2003030305	0080.EXP.09.0031	18,000	1.250	1.601–2.014
0875T001 (PRM)	0.875	3	HMX	400 [206]	0440	1.4D	2003030305	0080.EXP.09.0031	18,000	1.250	1.002–1.506
1000T001 (PRM)	1.000	3	HMX	400 [206]	0440	1.4D	2003030305	0080.EXP.09.0031	18,000	1.500	1.429–2.665
1188T001 (PRM)	1.188	6.25	HMX	400 [206]	0440	1.4D	2003030305	0080.EXP.09.0031	18,000	1.750	2.662–3.377
1250T001 (PRM)	1.250	7	HMX	400 [206]	0440	1.4D	2003030305	0080.EXP.09.0031	18,000	1.750	1.915–2.492
1375T001 (PRM)	1.375	7	HMX	400 [206]	0440	1.4D	2003030305	0080.EXP.09.0031	18,000	2.000	2.207–3.923

HMX explosive for all cutters rated at 400° for 1 hr.