

DRILL PIPE CUTTER SPECIFICATIONS

Part Number	Cutter OD (in.)	Net Explosive Content (g)	Explosive Class	Temperature Rating (°F) [°C]	UN ID	Hazard Class	EX (DOT) Number	EC Certificate	Pressure Rating (psi)	Pipe OD (in.)	Wall Thickness (in.)
2188T101 (RED)	2.188	36	HMX	400 [204]	0440	1.4D	2000090138	0080.EXP.09.0016	22,000	3½	0.375
2188T101 (PRM)	2.188	36	HMX	400 [204]	0440	1.4D	2000090138	0080.EXP.09.0016	22,000	3½	0.375
2251T101 (PRM)	2.251	36	HMX	400 [204]	0440	1.4D	2000090138	0080.EXP.09.0016	20,000	3½	0.476
3680T301 (RED)	3.680	59	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.09.0015	18,000	5	0.362
3680T201 (PRM)	3.680	59	HMX	400 [204]	0059	1.1D	2003030306	0080.EXP.09.0018	18,000	5	0.362
3680T201 (PRM)	3.680	59	HMX	400 [204]	0059	1.1D	2003030306	0080.EXP.09.0018	18,000	5	0.478
3680T301 (PRM)	3.680	59	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.09.0015	18,000	5	0.362
3680T301 (PRM)	3.680	59	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.09.0015	18,000	5	0.478
3800T301 (PRM)	3.800	76	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.09.0015	18,000	5	0.476
4070T301 (PRM)	4.070	76	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.09.0015	22,000	5½	0.500
4200T301 (PRM)	4.200	76	HMX	400 [204]	0440	1.4D	2013040285	0080.EXP.09.0015	18,000	5½	0.500

HMX explosive for all cutters rated at 400° for 1 hr.